

SWP-GS-0001

INSTALLATION OF SANDVIK MD & MDX ROCKBOLTS
SAFE WORKING PROCEDURE

Applicable parts – MD & MDX rock bolts and rock plates

Prepared by – B. Darlington

Date – 09/05/2012

Revised by – B. Darlington



Date – 13/02/2024

Resources	<ul style="list-style-type: none"> • 1 or 2 person(s) • Jumbo (or other bolting machinery) 	Materials	<ul style="list-style-type: none"> • Drill rod and bit (Ø43.0-45.0 mm) • Sandvik Bolt driver • MD/MDX Rock bolt • Sandvik Rock plate • Pull collar if pull test is required on MD/MDX bolt
PPE	<ul style="list-style-type: none"> • Gloves • Hearing protection • Steel cap boots • Safety glasses • Hard Hat • Underground Mine Site Minimum PPE 	Environment Controls	<ul style="list-style-type: none"> • Underground mine site safe working procedures • When working alone, always follow site specific procedures/requirements for communication whilst working alone




References	<ul style="list-style-type: none"> • SSP Sandvik Standard Procedure 002 – PPE. (In lieu of mine site PPE procedures) • SSP Sandvik Standard Procedure 006 – Manual Task. (In lieu of mine site Manual handling procedures).
-------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



General handling of MD & MDX Rockbolt product





	Steps	Potential Hazard & Consequences.	Control Measures	Visual
a)	Conduct Take 5 of the work area before starting the task.	<ul style="list-style-type: none"> Poor rock conditions. Slip, Trip and fall. Raised Boom may drop/fall. Poorly stored consumables. Vehicle could run in to bolt left on the ground. 	<ul style="list-style-type: none"> Never work under unsupported ground. Never enter unsupported ground Ensure work area is free from obstacle and tripping hazards. Do not leave bolts on the ground on the roadways. Never work under Jumbo Boom. 	
b)	Transporting and handling of MD & MDX Rock bolts should be performed with correct PPE and lifting techniques.	<ul style="list-style-type: none"> Heavy material, which can cause back /hand injuries. Strains /sprains. 	<ul style="list-style-type: none"> Ensure gloves are worn during installation. Follow mine site PPE Procedures. Follow mine site Manual handling procedures. Carry only 1 bolt at a time. 	<p>MD Bolt Masses</p> <ul style="list-style-type: none"> 1.8 m = 10.5 kg 2.1 m = 12.1 kg 2.4 m = 13.7 kg 3.0 m = 16.7 kg <p>MDX Bolt Masses</p> <ul style="list-style-type: none"> 1.8 m = 8.8 kg 2.1 m = 10.5 kg 2.4 m = 12.0 kg 3.0 m = 15.0 kg 3.8 m = 19.4 kg 4.0 m = 20.5 kg
c)	Transporting crates on rough roadways	<ul style="list-style-type: none"> Crate of bolt could get lose and bolts can slide sideways. 	<ul style="list-style-type: none"> Ensure locknut on the top bar of the crate is tightened before transportation 	
d)	Storage of MD & MDX Rock bolts.	<ul style="list-style-type: none"> Failure of MD & MDX storage crates if stored/stacked incorrectly. Fall of damaged/incorrectly stacked crates. Disposal of empty bolt crates 	<ul style="list-style-type: none"> Stack crates maximum 4 high; and only 1 high if crate is damaged or stacking on uneven ground Ensure empty crates are disposed of correctly and responsibly 	





	Steps	Potential Hazard & Consequences.	Control Measures	Visual
e)	Cutting of the PTFE straps on the MD and MDX crate	<ul style="list-style-type: none"> PTFE straps under pressure store energy Cutting or severing hazard when cutting the straps 	<ul style="list-style-type: none"> Ensure gloves and safety glasses are worn during cutting straps operation. Follow mine site PPE Procedures 	 <p>Safety Glasses Hand Protection</p>
f)	Removal of top bar from the MD and MDX crate	<ul style="list-style-type: none"> Correctly tightened top bar nuts create stored energy in bar Cutting or severing hazard when removing nuts with incorrect tools Manual handling when removing tight top bar Pry-bar may be required to lift top bar as bolts can nest into crate during transportation and cause a tight top bar 	<ul style="list-style-type: none"> Use correct tools (hex spanner) and slowly release nuts from top bar Use correct manual handling techniques to remove top bar Ensure correct gloves are worn when removing nut and top bar 	
g)	Opening the timber crates	<ul style="list-style-type: none"> Cutting or severing from incorrectly removed steel brackets Cutting or severing from using incorrect tools Manual handling when removing crate lid 	<ul style="list-style-type: none"> Do not cut or tear crate lid brackets Use Phillips head screw driver to remove screws from crate lid brackets Remove all steel brackets completely from crate lid and body Correct manual handling techniques 	



Installation of MD & MDX Rockbolt

	Steps	Potential Hazard & Consequences	Control Measures/procedures	Visual
a)	Insert Drill rod into first Jumbo Drifter.	<ul style="list-style-type: none"> Struck by moving boom. Crush finger/hand. Slip, trip, fall. 	<ul style="list-style-type: none"> Underground minimum PPE. Performed by competent person. Pre-start/take 5. Machine/boom isolation when working with boom. 	
b)	Attach Sandvik Bolt driver (and extension scroll bar if required) to second Jumbo Drifter.	<ul style="list-style-type: none"> Finger/hand crush injury. Splinters and sharp edges. Slip, trip, fall. Manual handling strain. Incorrect bolt driver (resin bolt driver) – possible failed installation. 	<ul style="list-style-type: none"> Competent person. Underground minimum PPE. Correct manual handling techniques. Correct driver (visual inspection for quality). Machine/boom isolation when working with boom. 	 <p style="text-align: center; border: 1px solid red; padding: 2px;">200 mm Driver with extension bar</p>
c)	Drill hole using drill bits of $\text{Ø}43.0\text{--}45.0$ mm, approximately 150 mm longer than bolt length. Hole must be drilled as perpendicular as practical to rock face.	<ul style="list-style-type: none"> Falling rock and projectiles. Oversized diameter hole (due to poor ground conditions or too large drill-bit) may result in poor ground support, which could result in poor bolt performance. 	<ul style="list-style-type: none"> Mine site drilling procedure. Guarding on Jumbo Correctly selected drill bit for ground conditions. 	 <p style="text-align: center; border: 1px solid red; padding: 2px;">$\text{Ø}43.0 - 45.0$ mm</p>
d)	Load MD/MDX bolt into the Boom, locating the blind nut in the driver, and place the rock plate on end of bolt (in-front of centraliser). If Pull-collar installation is required for MD/MDX bolt, this must be placed between the rock plate and the centraliser.	<ul style="list-style-type: none"> Finger/hand crush injury. Splinters and sharp edges. Slip, trip, fall. Manual handling strain. 	<ul style="list-style-type: none"> Underground minimum PPE. Performed by competent person. Correct manual handling techniques. Machine/boom isolation when working with boom. 	



	Steps	Potential Hazard& Consequences	Control Measures/procedures	Visual
e)	Drive bolt into hole using percussion and water. (CORRECT ALIGNMENT IS CRITICAL) (DO NOT USE ROTATION)	<ul style="list-style-type: none"> Poorly aligned bolts may result in damaged bolts or poorly supported ground. Any damaged/partially installed bolts must be remediated. Use of rotation will expand the wedges and the bolt will jam in the hole; resulting in incomplete installation. Noise Falling rock 	<ul style="list-style-type: none"> Correctly align bolt with pre-drilled hole. Do not use rotation. Underground minimum PPE (particularly hearing protection). Remain away from Boom operation area during this process. 	
f)	Tighten blind nut using Left-Hand rotation until the drifter stalls (Torque must be as close as practicable to 400 Nm). (CORRECT ALIGNMENT IS CRITICAL) (DO NOT USE PERCUSSION) (DO NOT USE RH ROTATION)	<ul style="list-style-type: none"> Use of percussion during tightening may result in breakage of bolt. Failure to stall drifter (bolt not functioned correctly). Poor boom misalignment could result in failure of re-bar/blind-nut from excessive cyclic loading. Falling components of broken bolt. RH rotation will result in failed bolt installation. Insufficiently tightened bolt may lead to compromised ground support due to insufficiently expanded wedges. Over tightened bolt may break the bolt or bolt components. 	<ul style="list-style-type: none"> Do not use percussion while tightening the nut. Do not use right hand (RH) rotation (can result in disengagement of wedges). Ensure correct boom alignment. If bolt does not stall the drifter, install secondary bolt adjacent to original (failed) bolt. Remain away from bolting area during this process. Ensure drifter is within the required torque range of 350-450 Nm. 	 <div data-bbox="1592 954 1951 1050" style="border: 1px solid red; padding: 5px;"> <p>Secondary bolt installed due to failed primary bolt.</p> </div>
g)	Disconnect the Driver from the bolt and proceed to install next bolt.	<ul style="list-style-type: none"> Falling rock and projectiles. 	<ul style="list-style-type: none"> Mine site drilling procedure. Guarding on Jumbo 	



	Steps	Potential Hazard& Consequences	Control Measures/procedures	Visual
h)	Disconnect the Driver from the bolt and proceed to install next bolt.	<ul style="list-style-type: none"> Falling rock and projectiles. 	<ul style="list-style-type: none"> Mine site drilling procedure. Guarding on Jumbo 	
i)	Failed bolt remediation (to be used when an MD or MDX bolt is not 100% inserted into the borehole). All failed bolts or exposed bolts after stripping to be either bent to lie flat with the rock or cut off, as required by site.	<ul style="list-style-type: none"> Release of stored energy (while bending bolt). Finger/hand crush injury. Manual handling strain. Hot work (if using oxy-cutter or angle grinder). Sharp edges – cuts/abrasions. 	<ul style="list-style-type: none"> Remain out of the line of fire. Use bolting machine to bend bolt. Follow site specific hot-work procedures. Ensure correct PPE is available and used. 	
j)	Pull testing of MD & MDX bolts	<ul style="list-style-type: none"> For hazard and controls refer to SWP-GS-0002 	<ul style="list-style-type: none"> For hazard and controls refer to SWP-GS-0002 	
k)	Bolt life	<ul style="list-style-type: none"> Certain ground conditions may elevate corrosion rates and effect bolt's component strength 	<ul style="list-style-type: none"> Regularly inspect ground support to ensure excessive corrosion is not present Carry out remediation if needed. 	



DOCUMENT HISTORY

The document status is detailed below (e.g. Concept, Final, Release)

Date	Version	Change(s)	Author
09/05/2012	0	Document released	B. Darlington
11/05/2018	1	Updates to boom operation area, drill bit diameter range updated, addition of MDX bolt and Step h).	B. Darlington
02/09/2019	2	Bolt type added where missing, drill bit diameters updated based on Bolt DRA August 2019.	B. Darlington
18/03/2022	3	Add mass for 3.8 m and 4 m MDX bolts Add crate transportation hazard Add hazard or rockbolts on roadways Changed suggested drill bit size	O. Vallati / S. Weaver
07/02/2023	4	Change based on DRA Feb. 2023: Add exposed bolt after stripping to be remediate (step h) Add "Never enter unsupported ground" (step a)	O. Vallati
19/06/2023	5	Add section 1 step f) regarding top bar removal	B. Darlington
13/02/2024	6	Add section 1 step g) regarding timber crate	B. Darlington